


ASUS

RT-AX88U Pro



Logout

Reboot

English

Quick Internet Setup

General

Network Map

AiMesh

Guest Network

AiProtection

Parental Controls

Adaptive QoS

Traffic Analyzer

Game

Open NAT

USB Application

AiCloud 2.0

Tools

Advanced Settings

Wireless

LAN

WAN

Amazon Alexa

IPv6

VPN

Firewall

Administration

System Log

Network Tools

Operation Mode: wireless router Firmware: 3004.388.8_4 SSID:

Internet Connection Dual WAN Port Trigger Virtual Server / Port Forwarding DMZ DDNS NAT Passthrough

WAN - Dual WAN

RT-AX88U Pro provides Dual WAN support. Select Failover mode to use a secondary WAN for backup network access. Select Load Balance mode to optimize bandwidth, maximize throughput, minimize response time, and prevent data overload for both WAN connections. [Dual WAN FAQ](#)

To enable WAN Aggregation go to the [WAN-Internet Connection page](#).

Basic Config

Enable Dual WAN	<div>ON</div>	
Primary WAN	<div>Ethernet LAN</div>	<div>2.5G/1G LAN</div>
Secondary WAN	<div>WAN</div>	
Dual WAN Mode	<div>Fail Over</div> <input type="checkbox"/> Allow fallback	

Auto Network Detection

Detailed explanations are available on the [ASUS Support Site FAQ](#), which may help you use this function effectively.

Detect Interval	Every <div>3</div> seconds	
Failover Trigger Condition	When the current WAN fails <div>2</div> continuous times, failover to Secondary WAN	
Network Monitoring	<input type="checkbox"/> DNS Query <input type="checkbox"/> Ping	

Apply

Help & Support Manual | Product Registration | App

FAQ

