



Quick Internet Setup

Operation Mode: wireless_router Firmware Version: 386.5_2
SSID: Rambali Rambali Fast



General

Network Map

AiMesh

Guest Network

AiProtection

Parental Controls

Adaptive QoS

Traffic Analyzer

Game

Open NAT

USB Application

AiCloud 2.0

Tools

Advanced Settings

Wireless

LAN

WAN

Alexa & IFTTT

IPv6

VPN

Firewall

Administration

System Log

Network Tools

Internet Connection

Dual WAN

Port Trigger

Virtual Server / Port Forwarding

DMZ

DDNS

NAT Passthrough

WAN - Dual WAN

GT-AX11000 provides Dual WAN support. Select Failover mode to use a secondary WAN for backup network access. Select Load Balance mode to optimize bandwidth, maximize throughput, minimize response time, and prevent data overload for both WAN connections. [Dual WAN FAQ](#)

To enable WAN Aggregation go to the [WAN-Internet Connection page](#).

Basic Config

Enable Dual WAN

OFF

Primary WAN

2.5G WAN

Auto Network Detection

Detailed explanations are available on the [ASUS Support Site FAQ](#), which may help you use this function effectively.

Detect Interval

Every 5 seconds

Internet Connection Diagnosis

When the current WAN fails 12 continuous times, it is deemed a disconnection.

Network Monitoring

DNS Query Ping

Apply

Search input field