

ASUSRT-AC68U

Powered by
Asuswrt-Merlin

Logout

Reboot

English

Quick Internet Setup

General

Network Map

AiMesh

Guest Network

AiProtection

Parental Controls

Adaptive QoS

Traffic Analyzer

Game

Open NAT

USB Application

AiCloud 2.0

Tools

Advanced Settings

Wireless

LAN

WAN

IPv6

VPN

Firewall

Administration

System Log

Network Tools

Addons

Operation Mode: wireless_router Firmware Version: 386.5_2 SSID: ASUS ASUS_5G

VPN StatusVPN DirectorVPN ServerVPN ClientTOR

OpenVPN Client Settings

OpenVPN PPTP/L2TP

Before starting the service make sure you properly configure it, including the required keys, otherwise you will be unable to turn it on.

In case of problem, see the System Log for any error message related to openvpn.

Client control

Select client instance1: NordVPN US6711 Standard UDP

Service stateONConnected (Local: 10.8.2.4 - Public:)Refresh

Automatic start at boot timeYesNo

DescriptionNordVPN US6711 Standard UDP

Import .ovpn fileChoose FileNo file chosenUpload

Network Settings

Interface TypeTUNTAPTAP

ProtocolTCPUDP

Server Address and PortAddress:Port: 1194

Create NAT on tunnelYesNo

Inbound FirewallBlockAllow

Accept DNS ConfigurationExclusive

Redirect Internet traffic through tunnelVPN Director (policy rules)

Killswitch - Block routed clients if tunnel goes downYesNo

Authentication Settings

Authorization ModeTLSSStatic Key

Username/Password AuthenticationYesNo

Username

Password

Username / Password Auth. OnlyYesNoWarning: You must define a Certificate Authority.

Crypto Settings

Keys and CertificatesEdit...

Data ciphersCHACHA20-POLY1305:AES-128-GCM:AES-256-GCM:AES-12

TLS control channel security (tls-auth / tls-crypt)Outgoing Auth (1)

Auth digestSHA512

Advanced Settings

Log verbosity3(Between 0 and 6. Default: 3)

CompressionNone

TLS Renegotiation Time0(In seconds, -1 for default)

Connection Retry attempts15(0 for infinite)

Verify Server Certificate NameNo

VPN Director rules related to this client

Enabled	Description	Local IP	Remote IP	Iface
	2.4GHz Guest 1	192.168.11.0/24		OVPN1
	5GHz1 Guest 1	192.168.14.0/24		OVPN1
	YazFi 2.4GHz 1	192.168.11.0/24		OVPN1
	YazFi 5GHz 1	192.168.14.0/24		OVPN1

Custom Configuration

remote-random
resolv-retry infinite
remote-cert-tls server
ping 15
ping-restart 0
ping-timer-rem
persist-key
persist-tun

DefaultApply

Help & Support

Manual

Product Registration

App

FAQ

2020 ASUSTeK Computer Inc. All rights reserved.