

Guest Network

AiProtection

Adaptive QoS

Traffic Analyzer

USB Application

AiCloud 2.0

Advanced Settings

Wireless

LAN

WAN

IPv6

VPN

Firewall

Administration

Steering Trigger Condition

Band	2.4GHz	5GHz-1	5GHz-2
Bandwidth Utilization	<div><div></div></div> 80%	<div><div></div></div> 80%	<div><div></div></div> 80%
Enable Load Balance	<input checked="" type="radio"/> Yes <input type="radio"/> No	<input checked="" type="radio"/> Yes <input type="radio"/> No	<input checked="" type="radio"/> Yes <input type="radio"/> No
RSSI	<div>Less</div> -58 dBm	<div>Less</div> -76 dBm	<div>Less</div> 0 dBm
PHY Rate Less	<div><div></div></div> Disable	<div><div></div></div> < 120 Mbps	<div><div></div></div> < 433 Mbps
PHY Rate Greater	<div><div></div></div> > 84 Mbps	<div><div></div></div> > 300 Mbps	<div><div></div></div> Disable
VHT	<div>All</div>	<div>All</div>	<div>All</div>

STA Selection Policy

RSSI	<div>Less</div> -58 dBm	<div>Less</div> -76 dBm	<div>Less</div> 0 dBm
PHY Rate Less	<div><div></div></div> Disable	<div><div></div></div> < 120 Mbps	<div><div></div></div> < 433 Mbps
PHY Rate Greater	<div><div></div></div> > 84 Mbps	<div><div></div></div> > 300 Mbps	<div><div></div></div> Disable
VHT	<div>All</div>	<div>All</div>	<div>All</div>

Interface Select and Quality Procedures

Target Band	1: 5GHz-2 2: 5GHz-1	1: 2.4GHz 2: 5GHz-2	1: 5GHz-1 2: 2.4GHz
Bandwidth Utilization	<div><div></div></div> 60%	<div><div></div></div> 60%	<div><div></div></div> 60%

Bounce Detect